

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A device adapted to communicate with an audio mux, the audio mux receiving a vocoder input from a vocoder and an audio decoder input from an audio decoder, the device comprising:
 - a stereo/mono control unit coupled to a codec; and
 - a plug-in detection circuit for determining a type of an audio output device coupled to an I/O jack and outputting the determined type of the audio output device to the stereo/mono control unit;wherein the determined type of audio output device is one of a stereo capable device and a mono capable device;
 - wherein the stereo/mono control unit receives an audio mux input identifying a type of a signal that the codec received from the audio mux, and the stereo/mono control unit provides a control output to the codec based on the determined type of the audio output device and the identified type of the signal.
2. (Original) The device of claim 1 wherein the control output is coupled to a plurality of components in a receive audio processing path of the codec.
3. (Previously Presented) The device of claim 2 wherein the plurality of components are in one of a right channel of the receive audio processing path and a left channel of the receive audio processing path.
4. (Cancelled)

5. (Original) The device of claim 2 wherein the control output disables at least one of the plurality of components to reduce power consumption in the receive audio processing path of the codec.
6. (Original) The device of claim 2 wherein the plurality of components comprise a receive gain, a receive filter, a digital-to-analog converter, a left/right selector, and a headset amp.
7. (Cancelled)
8. (Previously Presented) The device of claim 1 wherein the control output disables at least one of a plurality of components in a receive audio processing path of the codec when the identified type of the signal is a voice signal.
9. (Original) The device of claim 8 wherein the plurality of components comprise a receive gain, a receive filter, a digital-to-analog converter, a left/right selector, and a headset amp.
10. (Cancelled)
11. (Cancelled)
12. (Currently Amended) A method for processing received audio signals in a device, the method comprising:
 - determining a type of an audio output device coupled to an I/O jack;
 - determining a type of the received audio signals; wherein the received audio signals are received at the device for output to the audio output device, and wherein the type identifies whether a signal provided to an audio codec by an audio multiplexer is one of voice, stereo music, and mono music; and
 - providing a control output to disable or enable a first channel in a receive audio processing path based on the type of the audio output device and the type of the received audio signals.
13. (Previously Presented) The method of claim 12, further comprising:

disabling the first channel in the receive audio processing path and enabling a second channel in the receive audio processing path when the type of the received audio signals is mono signals; and

enabling the first channel in the receive audio processing path and enabling the second channel in the receive audio processing path when the type of the received audio signals is stereo signals, wherein the disabling of the first channel is performed by a stereo/mono control unit.

14. (Previously Presented) The method of claim 13 wherein the disabling of the first channel is performed by the control output of the stereo/mono control unit disabling at least one of a plurality of components in the first channel;

wherein one of the first channel is a right channel in the receive audio processing path and the second channel is a left channel in the receive audio processing path and;

the first channel is a left channel in the receive audio processing path and the second channel is a right channel in the receive audio processing path.

15. (Original) The method of claim 14 wherein the plurality of components comprise a receive gain, a receive filter, a digital-to-analog converter, a left/right selector, and a headset amp.

16. (Cancelled)

17. (Cancelled)

18. (Previously Presented) The method of claim 13 wherein the device comprises a vocoder and an audio decoder, wherein the vocoder provides voice signals to an audio mux, and wherein the audio decoder provides music signals to the audio mux.

19. (Original) The method of claim 18 wherein the stereo/mono control unit receives the audio signals from the audio mux.

20. (Previously Presented) The method of claim 12 wherein the type of the audio output device is a stereo output component.

21. (Original) The method of claim 20 further comprising disabling the first channel when the stereo output component is not coupled to the device.
22. (Previously Presented) An apparatus for selectively reducing power consumption in an audio codec that includes a plurality of components, the apparatus comprising:
- a stereo/mono control unit having a first input for receiving an audio multiplexer input that identifies whether a signal provided to the audio codec by the audio multiplexer is one of voice, stereo music, and mono music;
 - a second input for receiving a plug-in detection input that identifies whether an audio output device coupled an I/O jack is stereo capable or mono capable; and
 - an output for providing a control output; wherein the stereo/mono control unit generates the control output based on the audio multiplexer input and the plug-in detection input;
 - wherein the control output is provided to the audio codec and selectively reduces the power consumption in the audio codec.
23. (Previously Presented) The apparatus of claim 22 further comprising:
- an audio multiplexer, coupled to the stereo/mono control unit, for providing the audio multiplexer input to the stereo/mono control unit.
24. (Previously Presented) The apparatus of claim 22 further comprising:
- a plug-in detection circuit, coupled to the stereo/mono control unit, for providing the plug-in detection input to the stereo/mono control unit.
25. (Currently Amended) An apparatus for selectively reducing power consumption in an audio codec that includes a plurality of components, the apparatus comprising:
- means for determining a type of an audio output device coupled to an I/O jack;
 - means for determining a type of the received audio signals; wherein the received audio signals are received at the device for output to the audio output device, and wherein the type identifies whether a signal provided to the audio codec by the audio multiplexer is one of voice, stereo music, and mono music; and

means for providing a control output to disable or enable a first channel in a receive audio processing path based on the type of the audio output device and the type of the received audio signals.

26. (Previously Presented) The apparatus of claim 25, further comprising:

means for disabling the first channel in the receive audio processing path and enabling a second channel in the receive audio processing path when the type of the received audio signals is mono signals; and

means for enabling the first channel in the receive audio processing path and enabling the second channel in the receive audio processing path when the type of the received audio signals is stereo signals,

wherein the disabling of the first channel is performed by a stereo/mono control unit.

27. (Previously Presented) The apparatus of claim 26 wherein the disabling of the first channel is performed by the control output of the stereo/mono control unit disabling at least one of a plurality of components in the first channel;

wherein one of the first channel is a right channel in the receive audio processing path and the second channel is a left channel in the receive audio processing path, and the first channel is a left channel in the receive audio processing path and the second channel is a right channel in the receive audio processing path.

28. (Previously Presented) The apparatus of claim 25 further comprising:

means for disabling the first channel when a stereo output component is not coupled to the device.

29. (Currently Amended) A computer readable media embodying logic for processing received audio signals in a device, the logic configured to perform a method comprising:

determining a type of an audio output device coupled to an I/O jack;

determining a type of the received audio signals;

wherein the received audio signals are received at the device for output to the audio output device, and wherein the type identifies whether a signal provided to the audio codec by the audio multiplexer is one of voice, stereo music, and mono music; and

providing a control output to disable or enable a first channel in a receive audio processing path based on the type of the audio output device and the type of the received audio signals.

30. (Previously Presented) The computer readable media of claim 29, further comprising:
disabling the first channel in the receive audio processing path and enabling a second channel in the receive audio processing path when the type of the received audio signals is mono signals; and

enabling the first channel in the receive audio processing path and enabling the second channel in the receive audio processing path when the type of the received audio signals is stereo signals, wherein the disabling of the first channel is performed by a stereo/mono control unit.

31. (Previously Presented) The computer readable media of claim 30 wherein the disabling of the first channel is performed by the control output of the stereo/mono control unit disabling at least one of a plurality of components in the first channel;

wherein one of the first channel is a right channel in the receive audio processing path and the second channel is a left channel in the receive audio processing path and the first channel is a left channel in the receive audio processing path and the second channel is a right channel in the receive audio processing path.

32. (Previously Presented) The computer readable media of claim 31 wherein the plurality of components comprise a receive gain, a receive filter, a digital-to-analog converter, a left/right selector, and a headset amp.

33. (Previously Presented) The computer readable media of claim 29 further comprising disabling the first channel when a stereo output component is not coupled to the device.

34. (New) The method of claim 12,
wherein the type of the audio output device is capable of outputting a given type of audio signals, and
wherein the type of the received audio signals is determined to be different than the given type of audio signals
35. (New) The method of claim 12, wherein the receive audio processing path is not associated with audio signals received from the audio output device.
36. (New) The method of claim 12, further comprising:
disabling the first channel in response to the control output by reducing power at one or more components within the device.
37. (New) The method of claim 12,
wherein the type of the audio output device is determined to be stereo-capable, and
wherein the control output is provided to disable the first channel in the receive audio processing path.
38. (New) The method of claim 12, wherein the type of the received audio signals is determined to be stereo.